







DWN No.:
C-100163

proposal



Recommended PCB Layout

Item	Part name	Q'ty/Ea'	Material	Finish
1	HSG	1	High temp. Plastic UL94 V-0 Color Black	_____
2	Body	2	Leaded Brass	Gold plating over Nickel plating
3	Plunger	2	Leaded Brass	Gold plating over Nickel plating
4	Spring	2	Stainless steel wire	_____
5	CAP	1	High temp. Plastic UL94 V-0 Color Black	_____



TOP-LINK

Notes:

- 1 Dimensions shall be interpreted per ASME Y14.5M.
- 2 Mechanical performance(See the table 1)
- <2.1>The force is the average of forces obtained when plunger goes downwards and upwards.
- <2.2>Warning:Working height are not permitted to be less than Min working height.
- 3 Electrical performance
- Resistance: 30mOhm Max.
- Current rating: 2.0A
- 4 Packaging specification conforms to EIA 481
- 5 RoHS compliant.

Table 1 Mechanical performance

working height	6.50mm	80gf min
Durability	10000cycle	

100163-2

PART NUMBER

DIST

Update	2013/02/21
NEW	2007/08/28
Revision record.	Date.

Top-Link Electronics Ltd.	Type	Customer drawing	Unit	mm	Weight
TOLERANCES UNLESS OTHER SPECIFIED	DWN:	Cai wanlu	APVD:		
0.0 = ±0.15	CHK:	REL:			
0.00 = ±0.10					
0.000 = ±0.05	Angle: ±1°				
SURF. TEXTURE: REMOVE BURRS.	Name	POGO PIN	Customer drawing		
BREAK SHARP EDGES R0.05 MAX,DO NOT SCALE PRINT.	Scale	1:1	Size	A4	DWG No.
					C-100163
	Page	1/1	Rev.	A1	

Top-Link Electronics Ltd.