




DWN No.:
C-100100

proposal



Recommended PCB Layout




TOP-LINK

Notes:

- 1 Dimensions shall be interpreted per ASME Y14.5M.
尺寸标准遵从ASME Y14.5M.
- 2 Mechanical performance(See the table 1) (机械性能见表1)
<2.1>The force is the average of forces obtained when plunger goes downwards and upwards.
<2.1>弹力大小为产品下压和回弹时的平均值
<2.2>Warning: Working height are not permitted to be less than Min working height.
<2.2>工作高度不得低于标示的最小工作高度
- 3 Electrical performance (电气性能)
Insulation Resistance: 1,000MOhm minimum(绝缘电阻:1000M欧以上)
Dielectric Withstand Voltage: 500VAC/minute(抗电压:500VAC/minute)
Dynamic Resistance: 30mOhm Max:(between max and min working height)
工作范围内的动态电阻:30mOhm 最大
Current rating: 2.5A(额定电流:2.5A)
4 Packaging specification conforms to EIA 481
包装规范符合EIA 481
- 5 Working temperature (工作环境)
Withstanding Higt Temperature: 270℃(耐温: 270℃)
Operational Temperature: -40℃~+85℃(工作温度: -40℃~+85℃)
- 6 RoHS compliant.(产品符合RoHS标准)

Item	Part name	Q'ty/Ed	Material	Finish
1	HSG	1	High temp:Plastic UL94 V-0 Halogen-free Color Black	_____
2	Body	2	Leoded Brass	Au plating 0.1um min Ni plating 1.4um min
3	Plunger	2	Leoded Brass	Au plating 0.4um min Ni plating 1.4um min
4	Spring	2	Stainless steel wire	_____
5	CAP	1	High temp:Plastic UL94 V-0 Color Black	_____

Table 1 Mechanical performance		
working height	4.0mm	80gf Min <2.1>
Durability	10000cycle	



Cap for Vacuum Nozzle

Top-Link Electronics Ltd.		Type	Unit	Weight	PART NUMBER
TOLERANCES UNLESS OTHER SPECIFIED		Customer drawing	mm		100100-2
0.0 = ±0.15		DWN:	APVD:		
0.00 = ±0.10		CHK:	REL:		
0.000 = ±0.005		Angle: ±1°			
SURF. TEXTURE:		Name	Pogo pin connector		
REMOVE BURRS:		Scale	Size	DWG No.	Page
BREAK SHARP EDGES		1:1	A4	C-100100	1/1
RO.05 MAX.DD NOT SCALE PRINT.					Rev. C2

Top-Link Electronics Ltd.

A

B

C

D

4

3

2

1