




RECOMMEND PCB LAYOUT(TOP VIEW)
Layout Tolerance: $\pm 0.05\text{mm}$



TOP-LINK

- Notes:
- 1 Dimensions shall be interpreted per ASME Y14.5M
 - 2 Mechanical performance(See the table 1)
 - <2.1> The force is the average of forces obtained when plunger goes downwards and upwards
 - <2.2> Warning:Working height are not permitted to be less than Min working height
 - 3 Electrical performance
 - <3.1> Current rating: 2.0A
 - <3.2> Voltage rating: 36VAC/DC
 - <3.3> Dynamic Resistance:30mOhm Max (between max and min working height)
 - <3.4> Insulation Resistance:100MOhm minimum
 - 4 Environmental performance
 - <4.1> RoHS2.0 compliant
 - <4.2> Operating Temperature range:-40°C~+85°C
 - <4.3> Withstanding High Temperature:260°C/10Sec
 - 5 Packaging:Carrier tape

Table 1:Mechanical performance

Working Height	4.20mm	80-20gf
Durability	10000 Cycles Min.	

Top-Link Electronics LTD.		TOLERANCES UNLESS OTHER SPECIFIED	
0.0	= ± 0.25	0.0	= ± 0.15
0.00	= ± 0.10	0.000	= ± 0.05
Angle: $\pm 1^\circ$		SURE TEXTURE: Ra1.6	
REMOVE BURRS.		BREAK SHARP	
EDGES R0.05 MAX.			
Type		Customer drawing	Unit
DRW:		C.W/L	APRD:
CHK:		REL:	
Name		Pogo Pin Connector	
Scale	Size	Part NO.	Page
1:1	A4	100047-2	1/1
			Rev:
			D

top-link