


proposal



TOP-LINK

Notes:

- 1 Dimensions shall be interpreted per ASME Y14.5M.
- 2 Mechanical performance(See the table 1)
<2.1>The force is the average of forces obtained when plunger goes downwards and upwards.
- <2.2>Warning: Working height are not permitted to be less than Min working height.
- 3 Electrical performance
Resistance: 30mOhm Max.
Current rating: 2.0A
- 4 RoHS compliant.

Table 1 Mechanical performance

working height	4.00mm	135±35gf <2.1>
Durability	10000cycle	

Item	Part name	Qty/Ed	Material	Finish
1	Body	1	Leaded Brass	Au 0.1um plating Ni 1.4um
2	Plunger	1	Leaded Brass	Au 0.4um plating Ni 1.4um
3	Spring	1	Stainless steel wire	_____
4				
5				

2	Updated	2017/12/05
1	NEW	2012/05/08
Rev.	Revision record.	Date.

Top-Link Electronics Ltd.		Type	Customer drawing	Unit	mm	Weight	_____
TOLERANCES UNLESS OTHER SPECIFIED		DWN:	APVD:		Top-Link Electronics Top-Link Electronics Ltd.		
0.0 = ±0.15		Cai wanlu					
0.00 = ±0.10		CHK:	REL:				
0.000 = ±0.005							
Angle: ±1°							
SURF. TEXTURE: REMOVE BURRS. BREAK SHARP EDGES R0.05 MAX.IDO NOT SCALE PRINT.							
Name POGO PIN							
Scale	Size	DWG No.	Page		Rev.		
1:1	A4	C-20101010993	1/1		2		