



THIS INFORMATION IS CONFIDENTIAL AND IS DISCLOSED TO YOU ON CONDITION THAT NO FURTHER DISCLOSURE IS MADE BY YOU TO OTHER THAN TOP-LINK PERSONNEL WITHOUT WRITTEN AUTHORIZATION FROM TOP-LINK LTD.



DWG NO.
C-101437



Notes:
△ Material(材质):

- 1) Body : Brass
- 2) Plating : Brass
- 3) Solder : Stainless steel wire
- 4) Plating(电镀):
 - 1) Body Min 0.1um Gold plating over min. 1.4um Nickel plating (Body: 镀金0.1um Min 镍底1.4um Min)
 - 2) Plunger: Min 0.4um Gold plating over min. 1.4um Nickel plating (Plunger: 镀金0.4um Min 镍底1.4um Min)
- 3 Mechanical(机械性能):
 - 1) Force: 135±25gf per pin at 1.0mm stroke (压力: 1.0mm 的力: 135±25gf)
 - 2) Total stroke(总行程) : 1.20mm
 - 3) Durability(寿命): 10,000 cycle min.
 - 4) Electrical(电性能)
 - 1) Contact resistance(接触抵抗): 30mOhm Max.
 - 2) Voltage rating(额定电压): 36V DC Max
 - 3) Current rating(额定电流): 2.0A

TOP LINK

USED ON

-

101437-1

PART NUMBER

MATL	HT TR	FIN
△	—	—

DWN	APVD	Top-Link Electronics Ltd.
Qin		
CHK	REL	

NAME	PGGD	PIN
	PG-10-0.8-2.0-0.5-1.5-4.5-6.5	

SCALE	A4	DWG NO.	C-101437
1:1			

DIMENSIONS IN MM	TOLERANCES UNLESS OTHER SPECIFIED
0	= ±
0.0	= ±0.15
0.00	= ±0.10
0.000	= ±
ANGLE: ±1°	
SURF TEXTURE: 32/	
REMOVE BURRS, BREAK SHARP EDGES R0.05 MAX	
DO NOT SCALE PRINT	

NEW	REVISION RECORD	APVD	DATE
L TR			

4

3

2

1