


DWG NO.
C-101449

THIS INFORMATION IS CONFIDENTIAL AND IS DISCLOSED TO YOU ON CONDITION THAT NO FURTHER DISCLOSURE IS MADE BY YOU TO OTHER THAN TOP-LINK PERSONNEL WITHOUT WRITTEN AUTHORIZATION FROM TOP-LINK LTD.

LDC
-
DIST
-



Notes:
△ Material(材质):

- 1) Body : Brass
- 2) Plunger : Brass
- 3) Spring : Stainless steel wire
- 2 Plating(电镀):
 - 1) Body: Min 0.1um Gold plating over min. 1.4um Nickel plating (Body: 镀金0.1um Min 镍底1.4um Min)
 - 2) Plunger: Min 0.4um Gold plating over min. 1.4um Nickel plating (Plunger: 镀金0.4um Min 镍底1.4um Min)
- 3 Mechanical(机械性能):
 - 1) Force: 135±25gf per pin at 1.0mm stroke (弹力: 1.0mm 的力: 135±25gf)
 - 2) Total stroke(总行程) : 1.20mm
 - 3) Durability(寿命): 10,000 cycle min.
 - 4 Electrical(电性能)
 - 1) Contact resistance(接触抵抗): 30mOhm Max.
 - 2) Voltage rating(额定电压): 36V DC Max
 - 3) Current rating(额定电流): 2.0A

TOP LINK

NEW			2010/07/28
REVISION			
RECORD			
APVD			
DATE			
LTR			

DIMENSIONS IN MM				TOLERANCES UNLESS OTHER SPECIFIED			
0	= ±	-		0.0	= ±0.15		
0.00	= ±	0.10		0.000	= ±		
ANGLE: ±1°				SURF. TEXTURE: 32/			
REMOVE BURRS, BREAK SHARP EDGES R0.05 MAX				DO NOT SCALE PRINT			
NAME		PGGD PIN		SCALE		1:1	
PG-10-0.8-2.0-0.5-1.5-4.5-6.0		DWG NO.		A4		C-101449	
MATERIAL		HT TR		APVD		REL	
DWN		APVD		REL		REL	
CHK		REL		REL		REL	
FIN		FIN		FIN		FIN	
PART NUMBER		PART NUMBER		PART NUMBER		PART NUMBER	
101449-1		101449-1		101449-1		101449-1	

USED ON

-