



USED ON	
-	

Notes: $\triangleup$ Material (材质):

- 1)Body :brass
- 2)Plunge :Brass
- 3)Spring :Stainless steel wire
- 2 Plating(电镀):
 - 1)Body: Min 0.1um Gold plating over min. 1.4um Nickel plating (Body: 镀金0.1um Min 镍底1.4um Min)
 - 2)Plunger: Min 0.4um Gold plating over min. 1.4um Nickel plating (Plunger: 镀金0.4um Min 镍底1.4um Min)
- 3 Mechanical(机械性能):
 - 1)Force: 50 ± 10 gf per pin at 1.0mm stroke (力: 下压1.0mm的力: 50 ± 10 gf)
 - 2)Total stroke(总行程) : 1.30mm
 - 3)Durability(寿命): 10,000 cycle min.
- 4 Electrical(电性能)
 - 1)Contact resistance(接触抵抗): 30mOhm Max.
 - 2)Voltage rating(额定电压): 36V DC Max
 - 3)Current rating(额定电流): 2.0A

[illegible]

	修改公差		2010/08/02
	缩短0.5mm		2010/06/14
	NEW		2008/04/24
LTR	REVISION RECORD	APVD	DATE

DIMENSIONS IN MM				TOLERANCES UNLESS OTHER SPECIFIED		MATERIAL		HT TR		FIN	
0 = ±				0.0 = ±0.15		DWN		APVD		— ✓	
0.00 = ±0.10				0.000 = ±		QIN		REL		Top-Link Electronics Ltd.	
ANGLE: ±1°						CHK					
SURF. TEXTURE: 32/						NAME		PG-06 PIN			
REMOVE BURS, BREAK SHARP EDGES, R0.05 MAX						SCALE		DWG NO.		SHEET	
DO NOT SCALE PRINT						1:1		A4		C-101190	
								1 OF 1		REV C	

101190-1
PART NUMBER