



THIS INFORMATION IS CONFIDENTIAL AND IS DISCLOSED TO YOU ON CONDITION THAT NO FURTHER DISCLOSURE IS MADE BY YOU TO OTHER THAN TOP-LINK PERSONNEL WITHOUT WRITTEN AUTHORIZATION FROM TOP-LINK LTD.



DWN No.:
C-101211

DIST



Rev.	Renewal	2011/08/13
	NEW	2008/05/28
Revision record.	Date.	

Top-Link Electronics Ltd.		Type	Unit	Weight	PART NUMBER	
TOLERANCES UNLESS OTHERWISE SPECIFIED		Customer drawing	mm		101211-1	
0.0 = ±0.15		DWN:	APVD:			
0.00 = ±0.10		CHK:	REL:			
0.000 = ±0.005		Angle: ±1°				
SURF. TEXTURE: REMOVE BURRS.		Name	POGO PIN			
BREAK SHARP EDGES R0.05 MAX.DO NOT SCALE PRINT.		Scale	Size	DWG No.	Page	Rev.
		1:1	A4	C-101211	1/1	C

Table 1 Mechanical performance		
Max working height	3.90mm	80gf min <2.1>
Min working height	3.60mm	180gf Max
Durability	10000cycle	

Notes:

- 1 Dimensions shall be interpreted per ASME Y14.5M.
- 2 Mechanical performance(See the table 1)
- 3 Electrical performance
- 4 RoHS compliant.

Resistance: 30mOhm Max.Current rating: 2.0A

Item	Part name	Qty/Ed	Material	Finish
1	Body	1	Leaded Brass	Au 0.1um min plated over 1.4um min Ni
2	Plunger	1	Leaded Brass	Au 0.4um min plated over 1.4um min Ni
3	Spring	1	Stainless steel wire	_____
4				
5				