


THIS INFORMATION IS CONFIDENTIAL AND IS DISCLOSED TO YOU ON CONDITION THAT NO FURTHER DISCLOSURE IS MADE BY YOU TO OTHER THAN TOP-LINK PERSONNEL WITHOUT WRITTEN AUTHORIZATION FROM TOP-LINK LTD.



DWN No.:
C-101501




Table 1 Mechanical performance		
Working height	4.50mm	50±10 gf <2.1>
Durability	10000cycle	

Item	Part name	Q'ty/Ed	Material	Finish
1	Body	1	Leaded Brass	Au plating over Ni
2	Plunger	1	Leaded Brass	Au plating over Ni
3	Spring	1	Stainless steel wire	_____
4				
5				

TOP LINK

Not

1 Demnnsions shall be interpreted per ASME Y14.5M.

2 Mechanical performance(See the table 1)

<2.1> The force is the average of forces obtained when plunger goes downwards and upwards.

3 Electrical performance

Resistance: 50mOhm Max.Current rating: 2.0A

4 RoHS compliant.

Rev.	NEW	2011/07/01
Revision record.		
Date.		

Top-Link Electronics Ltd.		Type	Customer drawing	Unit	mm	Weight
TOLERANCES UNLESS OTHER SPECIFIED		DWN:	Qin zuozhong	APVD:	Top-Link Electronics Top-Link Electronics Ltd.	
0.0 = ±0.15		CHK:		REL:		
0.00 = ±0.10		Name				
0.000 = ±0.005		POGO PIN				
Angle: ±1°						
SURF. TEXTURE: REMOVE BURRS. BREAK SHARP EDGES R0.05 MAX. DO NOT SCALE PRINT.		Scale	Size	DWG No.	Page	Rev.
		1:1	A4	C-101501	1/1	A

4

3

2

1