



Spring : Stainless steel wire

Body: Min 0.1um Gold plating over min. 1.4um Nickel plating

Plunger: Min 0.4um Gold plating over min. 1.4um Nickel plating
(Plunger: 镀金0.4um Min 镍底1.4um Min)

Force: 120 ± 25 gf per pin at 1.0mm stroke

(力:下压1.0mm的力:120±25gf)

Total stroke(总行程): 1.40mm

4 Electrical (电性能)

1)Contact resistance(接触阻抗): 30mOhm Max.

2) Voltage rating (额定电压): 36V DC Max

3) Current rating (额定电流): 2.0A

DIMENSIONS IN MM
TOLERANCES UNLESS
OTHER SPECIFIED

MATL		HT TR	FIN
	1	—	—A

D/VN	APVD	<i>Top-Link</i> Electronics	Top-Link Electronics Ltd.
Q/n	REL		
CHK			

	NEW		2012/01/10
LTR	REVISION RECORD	APVD	DATE

ANGLE: $\pm 1^\circ$ 0.000				
SURF. TEXTURE: 3.2/ V REMOVE BURRS, BREAK SHARP EDGES. ROUNDS MAX DO NOT SCALE PRINT	NAME	PGDD	CONNECTOR 3 POSITIONS RIGHT ANGLE	
	SCALE	DWG	PGC-1.44-6.4-RA-3P-3.0PH	
	A4	NO.	C-100778	SHEET 1 OF 1
	1:1			REV 2