




DIST



Notes:
1 Dimensions shall be interpreted per ASME Y14.5M-1994.
2 Mechanical performance (See the table 2)
<2.1>The force is the average of forces obtained when plunger goes downwards and upwards.
<2.2>Warning: Working height are not permitted to be less than Min working height.
3 Electrical performance
Resistance: 30mOhm Max.; Current: 2A DC
4 Packaging Spec.
5 RoHS compliant.

Table 2 Mechanical performance			
The Min. working Stroke	0.7mm	Min 100gf	<2.1>
The Max. working Stroke	1.10mm	160±35gf	
Durability		10000 cycle	



Item	Part name	Qty/Ed	Material	Finish
1	HSG	1	High Temp. Plastic UL94 V-0 Color Black	
2	Body	4	Leaded Brass	Au plating 0.1um min Ni plating 1.4um min
3	Plunger	4	Leaded Brass	Au plating 0.4um min Ni plating 1.4um min
4	Spring	4	Stainless steel wire	
5				

C	Renewal	2017/10/11	Top-Link Electronics Ltd.	Type	Customer drawing	Unit	mm	Weight	
B1	Renewal	2016/07/25	TOLERANCES UNLESS OTHER SPECIFIED	DWN:	Caiwanzhu	APVD:			
B	Renewal	2011/12/28	0.0 = ± 0.15 0.00 = ± 0.10 0.000 = ± 0.05	CHK:	REL:				
A	NEW	2010/03/22	Angle: ±1° SURF. TEXTURE: REMOVE BURRS. BREAK SHARP EDGES R0.05 MAX. DO NOT SCALE PRINT.	Name	Customer drawing				
Rev.	Revision record.	Date.		Scale	Size	DWG No.	C-100594	Page	1/1
					A4			Rev.	C

100594-4
PART NUMBER